



- High efficiency stabilized power supplies
- Protection against short circuits
- Protection against overloads
- Cooling by free air convection
- Plate mounting: holes  $\varnothing 3,5$  mm and M3  
ALI5/24DIN: Omega/DIN rail mounting



	5 VDC $\pm 2\%$ 5 A	12 VDC $\pm 1\%$ 1.3 A	24 VDC $\pm 1\%$ 2.1 A	24 VDC $\pm 1\%$ 6.5 A
OUTPUT VOLTAGE				
INPUT VOLTAGE (*selectable)	85 ÷ 264 VAC 47 ÷ 63 Hz	85 ÷ 132 VAC* 170 ÷ 264 VAC* 47 ÷ 63 Hz	85 ÷ 132 VAC* 170 ÷ 264 VAC* 47 ÷ 63 Hz	88 ÷ 132 VAC* 176 ÷ 264 VAC* 47 ÷ 63 Hz
OUTPUT POWER	25 W	15.6 W	50.4 W	156 W
DC ADJUSTMENT RANGE	-5% +10%	-10% +10%	-10% +10%	-12% +16%
WORKING TEMPERATURE HUMIDITY (RH)	-10 °C +60 °C 20% +90%	-10 °C +60 °C 20% +90%	-10 °C +60 °C 20% +90%	-10 °C +60 °C 20% +90%
STORAGE TEMPERATURE HUMIDITY (RH)	-20 °C +85 °C 10% +95%	-20 °C +85 °C 10% +95%	-20 °C +85 °C 10% +95%	-20 °C +85 °C 10% +95%
FIXED SWITCHING FREQUENCY	37 Hz	37 Hz	27 Hz	25 Hz
DIMENSIONS	100x97x38 mm	100x97x38 mm	160x97x38 mm	200x110x50 mm
WEIGHT	390 g	310 g	510 g	800 g
CODE	ALIM5P190	ALI12STAB	ALI24STAB	ALI24STAB6A



	5 VDC $\pm 2\%$ 5.4 A	24 VDC $\pm 2\%$ 2 A	24 VDC $\pm 5\%$ 1 A
OUTPUT VOLTAGE			
INPUT VOLTAGE (*selectable)	85 ÷ 264 VAC 47 ÷ 63 Hz	85 ÷ 264 VAC 47 ÷ 63 Hz	100 ÷ 240 VAC 47 ÷ 63 Hz
OUTPUT POWER	25 W	48 W	24 W
DC ADJUSTMENT RANGE	-5% +10%	-6% +10%	-
WORKING TEMPERATURE HUMIDITY (RH)	-10 °C +60 °C 20% +90%	-10 °C +60 °C 20% +90%	0 °C +40 °C 10% +90%
STORAGE TEMPERATURE HUMIDITY (RH)	-20 °C +85 °C 10% +95%	-20 °C +85 °C 10% +95%	-20 °C +60 °C 10% +90%
FIXED SWITCHING FREQUENCY	37 Hz	37 Hz	-
DIMENSIONS	93x78x67 mm	93x78x67 mm	72x43x37 mm
WEIGHT	310 g	310 g	150 g
CODE	ALI5DIN5A	ALI24DIN2A	ALI24SPINA1AUN ALI24SPINA1AJACKUN