BIL2B

BENCH COUNTING SCALES - REMOTE PLATFORM INPUT

LAUMAS®





Counting scales connectable to remote weighing platform for weighing and counting of the large quantities:

- ACN / AIN / MN single cell platforms
- P / P-INOX 4 cells platforms

CAPACITY kg	DIVISION (g)	NET WEIGHT (kg)
6	e=0.1	4.8
15	e=0.2	4.8
30	e=0.5	4.8

DESCRIPTION

- Stainless steel plate.
- RS232 output for connection to PC or external printer.
- Remote platform input (connector included).
- 3x 6-digit backlit LCD display (20 mm height).
- 20-key waterproof keyboard.
- Bubble level and adjustable feet.
- 6 V rechargeable internal battery, 4 Ah capacity.
- Operating time: 70 hours.
- External battery charger 100-240 VAC included.
- Auto power-off.

MAIN FUNCTIONS

- Piece counting with simultaneous display of: number of pieces, average unit weight, total weight of the pieces on the scale.
- 100 storable items (PLU) with the following parameters: name, preset tare value, average unit weight.
- Automatic/manual totalization of the weighings.
- Weight indication as a percentage.
- Weight/pieces/percentage checking (HIGH/LOW) with acoustic and visual alarm.
- Optional receipt printing via STAVT II external printer: customizable header, date, time, item name, scale ID, scale type, net weight, average unit weight, number of pieces on the scale, total weight, total number of pieces.

CERTIFICATIONS

UK CA Equivalent of the CE marking for the United Kingdom

CERTIFICATIONS ON REQUEST
Calibration report


Rev. 0.0

BIL2B

BENCH COUNTING SCALES - REMOTE PLATFORM INPUT

LAUMAS®

DIMENSIONS (mm)



STAINLESS STEEL LOADING PLATE

TECHNICAL FEATURES

Power supply	100-240 VAC
Internal battery	6 V, 4 Ah capacity
Linearity	<0.01% full scale
Display resolution	60000
Units of measure	g, kg
Serial port	RS232
Remote platform input	5-pin circular connector (included)
Baud rate	600, 1200, 2400, 4800, 9600 (bit/s)
Humidity (condensate free)	<85%
Storage temperature	-10 °C +50 °C
Working temperature	0°C +40°C

OPTIONS ON REQUEST

	DESCRIPTION
	PIATTOBAC Stainless steel deep tray; dimensions: 230x300x40 mm.
	Rechargeable battery 6 V, 4.5 Ah capacity.
	STAVTII Desktop thermal printer.

The Company reserves the right to make changes to the technical data, drawings and images without notice.

Rev. 0.0

LAUMAS S.r.l.
Fax: (+39) 0521 681091
• SALES DEPARTMENT: sales@laumas.it
• Phone: (+39) 0521 683124

ISO 9001
ISO 14001

www.laumas.com