








	DESCRIPTION	CODE
CABLES AND SHEATHES		
	<p>6x0.25 mm² shielded cable. Available coils: 5 - 10 - 200 m.</p>	CAVO6020S
	<p>6x0.22 mm² anti-rodent armored shielded cable. Available coils: 5 - 10 - 200 m.</p>	CAVO6020SARM
	<p>Flexible PVC GUA sheath, installed on the load cell cable. IP67 - inner Ø: 10 mm - outer Ø: 14 mm.</p> <ul style="list-style-type: none"> ■ length 3 m + 1 PVC end-fitting ■ length 5 m + 1 PVC end-fitting ■ length 6 m + 1 PVC end-fitting ■ length 10 m + 1 PVC end-fitting 	
	<p>6x0.22 mm² shielded extension cable, sheathed, for connecting the weighing instrument to the junction box. PVC flexible sheath - IP67. Wiring by the customer.</p> <ul style="list-style-type: none"> ■ length 5 m + 1 M16x1.5 PVC end-fitting ■ length 10 m + 1 M16x1.5 PVC end-fitting 	
WIRINGS		
 <p>CONNECTIONS</p>	<p>Wiring between load cell and junction box.</p> <p>Wiring between weighing instrument and junction box.</p>	
SELECTOR SWITCHES		
	<p>External 12-position selector switch for selecting formulas and setpoint groups.</p>	EC
	<p>12 groups selection by 5 setpoint via external contact.</p>	E